Tools

Tools

493820 Drain Wrench

The 493420 Drain Wrench is used for installation and removal of the Emco Wheaton A1004EVR Spill Containment drain valves.

494240 Adapter Torque Wrench

The 494240 is used to verify the static torque of the swivel adapter in accordance to CARB Test Procedure TP.201.1B



566675 Drill Fixture

The 566675 Drill Fixture is used to accurately drill the rivet holes on the top drop tube for the Emco Wheaton A1100EVR collar assembly.

A0081-004CL Cam-Lock Wrench

The A0081-004CL Cam-Lock Wrench is used to install and remove the A0716 Composite Manhole cam-lock lids.

569427 Euro Lift Handle

The 569427 Euro Lift Handle fits into the keyhole to lift the A0716 Composite Manhole cam-lock lids.

Test Equipment

Test Equipment

A0081-1100 A1100 Testing Tool

The A0081-1100 Testing Tool is used to quickly and easily test the A1100-T series Testable Overfill Prevention Valve, without removing the valve from the riser.



A0081 Test Cover

The A0081 Test Cover is used with the Emco A1004-210TEST to perform vacuum testing on spill containment.

Part No.	Spill Containment	Diameter	Lbs.
A0081-12TEST	A1005-505 Series	12.40"	4.5
A0081-13TEST	A1004-316/517 Series	13.13"	4.5
A0081-15TEST	A1004-210 Series	15.25"	4.7
A0081-17TEST	A1004-215 Series, A1005-505CP	17.38"	5.0



A0099-001TEST Vapor Test Cap

The A0099-001TEST Vapor Test Cap is used when performing a pressure decay test. The cap incorporates the same features as the A0099-002 Vapor Cap. The extended tube underneath the cap opens the poppet on the vapor adapter. Pressure is injected through the Schrader valve, and a gauge can be connected to the barbed fitting.

A1004-210TEST Vacuum Apparatus w/Test Adapter

The A1004-210TEST is designed to perform vacuum testing on interstitial space in double wall spill containment. 5 lbs.

Model No.	Description
A1004-210TEST 494343 569143 569194 569195	Vacuum Test Apparatus Test Adapter Test Cap Assembly Air Switch 1/8" Air Regulator 1/8"









