
Extractor Fittings

A0079 Float Valve Extractor

The Emco Wheaton A0079 Extractor Assembly consists of a cast iron extractor body and an internal "bar style" cage. This cage holds any length of A0075 Ball Float (sold separately). The A0079 may be ordered with a variety of port combinations to accommodate tank venting and Stage II vapor recovery piping. The A0079 is also available without an extractor cage.

The A0079 Extractor Assemblies are avaliable in Stainless Steel for compatibilty with E85, DEF, and Bio-Diesel fuels.

The A0079 may be installed as part of the Emco Phase I EVR System without violating the Executive Order (VR-105)



CARB Executive Order G-70-97-A ULC MH24242

	Top/Bottom	Outlet Threads	Cage	I	
Model No.	Threads	A & B	Thread	Lbs.	
Cross Style					
A0079-050	4" NPT	2" × 2" NPT	N/A	8.5	
A0079-043	4" BSPT	2" × 2" BSPT	N/A	8.5	2" × 2" Outlet Threads
A0079-020 with Cage	4" NPT	2" × 2" NPT	2" NPSM	10.7	Outlet Threads
A0079-028 with Cage	4" BSPT	2" x 2" BSPT	2" NPSM	9.6	न
A0079-051	4" NPT	3" × 2" NPT	N/A	10.8	3" × 2"
A0079-051SS**	4" NPT	3" × 2" NPT	N/A	12.1	Outlet Threads
A0079-019 with Cage	4" NPT	3" × 2" NPT	2" NPSM	11.9	
· ·					
A0079-052	4" NPT	3" x 3" NPT	N/A	11.8	3" × 3"
A0079-025 with Cage	4" NPT	3" × 3" NPT	2" NPSM	12.0	Outlet Threads
Tee Style					
A0079-150	4" NPT	2" NPT	N/A	7.1	
A0079-150SS**	4" NPT	2" NPT	N/A	10.9	2" Outlot
A0079-120 with Cage	4" NPT	2" NPT	2" NPSM	10.7	2" Outlet Threads
A0079-122 with Cage	4" BSPT	2" BSPT	2" NPSM	8.5	Threads
					TT
A0079-152	4" NPT	3" NPT	N/A	8.7	211.0
A0079-152SS**	4" NPT	3" NPT	N/A	10.5	3" Outlet Threads
A0079-119 with Cage	4" NPT	3" NPT	2" NPSM	8.5	Threads
					8

Model No.	Top/Bottom Threads	Outlet Threads A	Cage Thread	Lbs.
A0079-444*	4" NPT	4" NPT	N/A	8.7
A0079-444M* (Male Base)	4" NPT	4" NPT	N/A	10.1
A0079-444SS* **	4" NPT	4" NPT	N/A	12.5

^{*}Used in Remote Fill applications only; does not support a cage

**Stainless Steel

